

# ClariNorit - 850R

## APPLICATIONS

- Waste Water Treatment
- Hydrocarbon Removal
- Remediation Treatment
- Toxin Removal

## FEATURES/BENEFITS

- Recycled Material
- Reduced Carbon Footprint
- High Activity
- High Hardness
- Low Dust

## PACKAGING

- 1000 pound bulk bags
- Bulk

## ClariNorit

Phone 210-525-7931

**ClariNorit- 850R** is a steam reactivated carbon produced at the newest reactivation facility in North America. This granular carbon has excellent adsorptive properties for removing organics and hydrocarbons from waste water as well as remediation sites.

**ClariNorit - 850R** is available in various packaging types and can part of a turnkey service.



## Specifications

Iodine Number	Minimum	850
Ash Content	Maximum	5%
Moisture Content	Maximum	5%

## Typical Properties

Ball Pan Hardness	85
Bulk Density	30 lbs/ft <sup>3</sup>

## Mesh Size

> 8 mesh	Maximum	5%
< 40 mesh	Maximum	5%
< 100 mesh (dust and fines)	Maximum	0.5%

**CAUTION:** Activated Carbon can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Use proper breathing apparatus to prevent prolonged dust exposure.

**NOTICE** ClariNorit reserve the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and carbon selection. ClariNorit or any of its affiliations assumes no obligation or liability for the usage of the information in this datasheet. No guarantees or warranties, expressed or implied, are provided and the user must accept full responsibility for performance of carbon based on this data.